

Beam LED Canopy Light Gen3

Bid farewell to fluorescent canopy lighting! Our Beam LED Canopy Light is the more energy-efficient alternative, with no damaging UV rays and virtually no heat to degrade packaging. With a lens specially designed for optimum light distribution, BEAM will literally put your merchandise in the best light, attracting more shoppers and boosting your sales.

- 3' and 4' lengths (914 mm and 1219 mm; other sizes available as special order)
- Maintenance-free life in excess of 50,000 hours (11 years at 12 hours/day)
- Uses same Power Supply and Jumper Cables as LEDge Light
- Durable aluminum extrusion
- Integrated magnets make installation on metal shelves or other surfaces easy and allow fast changes
- End tabs with holes for fastening to wood canopy and metal canopy brackets
- Certified by the DesignLights™ Consortium (DLC) and Underwriters Laboratories, Inc. (UL)
- DLC certification provides potential utility rebates
- All plug 'n play connections– no electrician required (Class 2 system)
- Multiple units are connected using Jumper Cables or Harness Assembly
- May be daisy-chained to single power supply for “single row” applications
- 100W power supply can power up to six 48" (1219 mm) lights
- Color temperature: 4,200K
- Color Rendering Index (CRI) of 85
- Contains no heavy metals
- Low power consumption helps meet California Title 24 lighting regulations
- Safe 24 volt DC system
- 3-year warranty
- Not compatible with Lumi-M-Stick, Lumiback, or Lumishelf™ accessories

LLB(NL)

LLB.....Beam LED Canopy Light
 NL.....Nominal Length 36" or 48"
 (914 mm or 1219 mm)



Gen3 LED Lighting Wattage					Output/Efficiency	
Shelf Width	Part Number	Actual Length	DC Watts	Max # Lights per Power Supply	Lumens	Lumens/Watts
36"	LLB36	34½"	11.3W	8	1444	128
48"	LLB48	46½"	15.0W	6	1925	128

Lights Per Circuit*		
Circuit Amps	Power Supplies	LLB48 per Circuit
15	8	48
20	11	66

* Above assumes fully loaded power supply

