

maxi line shelves & accessories

Flush Front Upper Shelf^A

- Smooth, dust-free edge ideal for merchandising without tag molding
- Versatility of three positions: Flat, 15° downslope, 30° downslope · Load capacity, flat position:
- 6" (152 mm) to 8" (203 mm) depths = 300 lbs 10" (254 mm) to 24" (610 mm) depths = 500 lbs 26" (660 mm) to 30" (762 mm) depths = 400 lbs
- Load capacity, 15° downslope position: 6" (152 mm) to 24" (610 mm) depths = 125 lbs 26" (660 mm) to 30" (762 mm) depths = 200 lbs
- Load capacity, 30° downslope: All shelf depths reduced to 100 lbs
- · Load capacities based on evenly distributed static loading

Bullnose Upper and Base Shelf^A

- Same form, fit, and function of Standard Upper Shelf, allowing the use of front fence and dividers
- Fits 1" OC slotting
- Radius front measures 11/4" (32 mm) high
- Maximum load capacities of Upper Shelf: 8" (203 mm) = 300 lbs 10" (254 mm) to 24" (610 mm) = 500 lbs 26" (660 mm) to 30" (762 mm) = 400 lbs
- Capacity reduced by 30% when front half is loaded (see product safety pages on loading in General Information)
- Maximum load capacity of Base Shelf is 600 lbs
- Load capacities based on evenly distributed static loading
- For additional load capacities, see Base Load Levelers
- Available in variety of finishes

Thin Profile Shelf, **Regular-Duty**

- Add merchandising space to every section
- Slimness of shelf allows additional row of shelves
- Excellent for displaying small merchandise
- Pushers required for optional merchandise display
- Ideal for tightly-spaced and lightweight merchandise

Thin Profile Shelf, **Light-Duty**

- Madix's thinnest profile shelf
- Slimness of shelf allows additional row of shelves
- Angled tag molding creates attractive pricing display
- No pushers required to display merchandise
- Ideal for tightly-spaced and lightweight merchandise


FF(TYPE)S-(NW)(ND)


FF Flush Front

- TYPE..... U=Upper
 - B=Base
 - S. Shelf
- NW..... Nominal Width 3' or 4' (914 mm or 1219 mm)
- ND..... Nominal Depth 12" to 30" in 2" increments (305 mm to 762 mm in 51 mm increments)

S(TYPE)SBN(NW)(ND)

- S..... Standard
- TYPE..... U=Upper
- NW..... Nominal Width 24" to 48" in 6" increments (610 mm to 1219 mm in 152 mm increments)
- ND..... Nominal Depth 12" to 30" in 2" increments (305 mm to 762 mm in 51 mm increments)





Bullnose Base Shelf ******

PLSTTS(NW)(ND)


- PLSTTS Thin Profile Shelf, Regular-Duty
 - NW..... Nominal Width 36" or 48" (914 mm or 1219 mm)
 - ND..... Nominal Depth 10" to 20" in 2" increments (254 mm to 610 mm in 51 mm increments)





PLSTTSLD(NW)(ND)

- PLSTTS Thin Profile Shelf
 - LD Light-Duty
 - NW..... Nominal Width 36" or 48" (914 mm or 1219 mm)
 - ND..... Nominal Depth 10" to 20" in 2" increments (254 mm to 610 mm in 51 mm increments)





B=Base S..... Shelf

BN..... Bullnose